

# Nova



Fig. 1

### To Set-up the Table:

• Place the folded table sitting on the rubber bumpers; with the heel of your hand, bump the tab between the face rest outlets and the table will open. (Fig. 1)



Fig. 2

• Open the table up until the legs are fully extended. Remove the face rest. (Fig. 2)

### To Set the Table Upright:

• When the table is fully opened, tilt the table upright until all four feet are on the floor. Lift one end of the table, press down on the middle and tension the cables a little. (Fig. 3)



Fig. 3

### To Change the Table Height:

• Choose the hole that represents the desired height and after removing the knob, put the bolt through that hole. Replace and tighten the knob by hand until snug. Repeat on all other leg extensions, setting all extensions at same height. (Fig. 4)



Fig. 4



Fig. 5

### To Close the Table:

• Turn the table on its side with the rubber bumpers down. If you have a face-rest, store it under the table by pushing the insertion dowel down into the clip provided. (Fig. 5)



Fig. 6

Partially close the table top.

• Fold the legs into the table and make sure the armrest is laying flat and the cables are inside of the table. Push the two halves of your table together to lock. (Fig. 6)




Fig. 8a

### For Tables with the Shiatsu Option:

• With your table on its side, release the cables from the rings (Fig. 8a) and turn the unlock clasp to the side. (Fig. 8b)



Fig. 8b

• Fold the legs against the underside and lay the table down flat on the floor. (Fig. 9)



Fig. 9

• To return to normal height settings, see the separate CAUTION label that refers to the Shiatsu Cable Option.



15704713 NVL3272473PLTTVN Ser#: NVS367130  
B Loc: SH Product: Nova LS3 27 x 24-34 x 73 PL/TT/VN  
TTCloud W: 27 H: 24-34 L: 73 Foam: PL 8/8/2007  
Order#: 500441 Line: Notes:

**CAUTION**  
Dynamic Load Rating:  
**450 lbs.**

**Handcrafted in the U.S.A.**  
Inspected By: \_\_\_\_\_

Oakworks®  
Original



All portable tables:  
SlideLock™:  
Unilock

U.S. Patent 5,009,170  
U.S. Patent 5,943,965  
Patent Pending

Part No. 1653

04/04

OAKWORKS®, Inc.

923 East Wellspring Rd., New Freedom, PA 17349

Toll Free Phone: 800-558-8850

Phone: 717-235-6807

Toll Free FAX: 877-562-4787

FAX: 717-235-6798

