here =s what nick gave me

hope this helps. Let =e know if you need anything =lse

Remove TITAN =eference 1080pRemove TITAN =eference 1080p 3D   Remove =IGHlite Cine 260 HC
        110-016
Aspect =atio   16x9   16x9   2000
20000
Display =ype   DarkChip™ DMD   DarkChip™ DMD   DarkChip™ =MD
36
Fill =actor   87.00   87.00   Not =pplicable
HDTV =ormat   1080p, 1080i, 480p, 720p, 480i, 576p, 576i   1080p, =080i, 480p, 720p, 480i, 576p, 576i   1080p,
=080i, 720p, 576p, 576i, 480p, 480i
Horizontal Scan Rate   15kHz to 100kHz   15kHz to =00kHz   Not applicable
Humidity   20 to 80% non-condensing   20 to 80% =on-condensing   20% to 85%
Lens =ount   Zoom: Motorized horizontal and vertical lens shift, zoom and =ocus. Fixed: Manual Focus.   Zoom:
Motorized horizontal and =ertical lens shift, zoom and focus. Fixed: Manual Focus.   Not =pplicable
Mechanical Mounting   Front/Rear Table, Front/Rear Ceiling, =djustable Front/Rear FeetFront/Rear Table, Front/Rear
Ceiling, =djustable Front/Rear Feet   Front/Rear Table, Front/Rear Ceiling, =djustable Front/Rear Feet
Native =esolution   1920 x 1080 Pixels   1920 x 1080 Pixels   1920 x 1080 =ixels
Operating =emperature 0 to 40°C   0 to =0°C   0 to 40 C
Power =onsumption   850   850   110-120/200-240 VAC
Remote =ontrol Remote wireless IR, Wired through 3.5mm stereo jack   Remote =ireless IR, Wired through 3.5mm
stereo jack   Remote =ireless IR
Safety =egulation   CE, CCC CE, CCC CE, FCC =lass A, UL
1500
Vertical =can Rate   24Hz to 85Hz   24Hz to 85Hz   43-85 =Z
Video Compatibility   HDTV, NTSC, =AL-M, PAL, NTSC 4:43, PAL-N, SECAM, HDCP Compliance   HDTV, NTSC, =AL-M,
PAL, NTSC 4:43, PAL-N, SECAM, HDCP Compliance   HDTV, NTSC, =AL, SECAM, PAL-N, HDCP Compliance
Video Processing   Enhanced =even-point Color Correction, Xenon Color Mode, User-selectable preset =nd
downloadable parametric de-gamma, Pixel-based motion adaptive =nterpolation, Class-leading de-interlacing using 3:2
and 2:2 =xtraction, Frame Delay: as low as 1 frame, source, Auto mode selection = plug and play setup   Enhanced
Seven-point Color Correction, =enon Color Mode, User-selectable preset and downloadable parametric =e-gamma,
Pixel-based motion adaptive interpolation, Class-leading =e-interlacing using 3:2 and 2:2 extraction, Frame Delay: as low
as 1 =rame, source, Auto mode selection - plug and play setup   Automation Control   RS232 9-pin D sub / RJ45 LAN
        RS232 9-pin = sub / RJ45 LAN   RS232 9-pin D sub / RJ45 =AN
Computer =ompatibility Up to 1920 x 1080   Up to 1920 x =080   Up to 1920 x 1080
Height in =nches   10.00   10.00   218.60
Length in =nches   26.00   26.00   500.60
Width in =nches   21.50   21.50   499.20
Weight in =ounds   68.00   68.00   WeightKg   31.00   31.00   Not =pplicable
=

1