

From: [REDACTED]

To: "Je vacation" <jeevacation@gmail.com>

Subject: Fw: Sub-woofer

Date: Tue, 22 Oct 2013 15:23:57 +0000

Importance: Normal

Jeffrey,

I just landed in palm bch, I need to obtain Ferry Permit for GII closing with FAA in Fort Lauderdale,,

Here is explanation why Eric shop didn't wire SUBs /out of receiver:

Larry,

>
> We contacted the engineer and asked the question about the sub out.
> His response - the sub out was not used because the car audio head unit
> needed to be integrated to the existing cabin audio equipment and it would
> not have worked through the headphone amplifier.
> To put this in the clearest way possible the JVC unit does not go directly
> to the car audio amplifiers that were installed. It goes to the aircraft's
> headphone amplifier and then to the volume control module allowing the page
> system to cut / override the system in the event of an emergency, and volume
> control for the master switch's as well as audio selection. Then it feeds
> back to the amps and out to the speakers. By hooking up the subwoofer out
> (which is one RCA instead of the required two) the cross feed to the
> speakers would be uncontrollable. By using the RCA outs front and Rear it
> is possible to control the bass both at the head unit and at the amplifiers.

>
>
> DANIEL GAROFALO | AVIONICS
>
> P [REDACTED] F [REDACTED] | [REDACTED] | www.intljet.com

-----Original Message-----

From: Jay Massar
To: Lawrence Visoski
To: Eric Roth
To: Dan Garofalo
Subject: Sub-woofer
Sent: Oct 22, 2013 10:00 AM

>
> We contacted the engineer our and asked the question about the sub out.
> His response - the sub out was not used because the car audio head unit
> needed to be integrated to the existing cabin audio equipment and it would
> not have worked through the headphone amplifier.
> To put this in the clearest way possible the JVC unit does not go directly
> to the car audio amplifiers that were installed. It goes to the aircraft's
> headphone amplifier and then to the volume control module allowing the page
> system to cut / override the system in the event of an emergency, and volume

> control for the master switch's as well as audio selection. Then it feeds
> back to the amps and out to the speakers. By hooking up the subwoofer out
> (which is one RCA instead of the required two) the cross feed to the
> speakers would be uncontrollable. By using the RCA outs front and Rear it
> is possible to control the bass both at the head unit and at the amplifiers.

>
>

> DANIEL GAROFALO | AVIONICS

>

> P [REDACTED] | F [REDACTED] | [REDACTED] | www.intljet.com

>

> -----

> -----

> 2221 Smithtown Avenue, Long Island MacArthur Airport, Ronkonkoma, New York, 11779

>

> On Oct 22, 2013, at 8:05 AM, [REDACTED] wrote:

>

>> Hello Eric, Jay and Dan,

>> Jeffrey needs an explanation why the "Sub-out" was not utilized during
> this install. Having Sub woofer out operational would give better control on
> BASS, especially since we are getting a BASS freq to the PSU speakers.

>> Jeffrey needs an email today explaining why SUB/OUT is inop per the
> install please.

>> Copy jeffrey and I on this email Dan, thx.

>>

>> Thx

>> Larry

>> Sent via BlackBerry by AT&T

>

>

Sent via BlackBerry by AT&T