



Quote 200126-01

August 7, 2018

HBRK Associates Inc

Attention:Richard

Dear Richard, Thank you for this opportunity to quote Caterpillar products for your business needs. We are pleased to quote the following for your purchase consideration.

One (1) New CATERPILLAR Model: 325FL TC Hydraulic Excavators with all standard equipment in addition to the additional specifications listed below:

**STOCK NUMBER:**C90294      **SERIAL NUMBER:**0NDJ20459

We wish to thank you for the opportunity of quoting on your equipment needs. This quotation is valid for 30 days, after which time we reserve the right to re-quote. If there are any questions, please do not hesitate to contact me.

Sincerely,

Jay West  
Machine Sales Representative

**One (1) New CATERPILLAR Model: 325FL TC Hydraulic Excavators with all standard equipment in addition to the additional specifications listed below:**

**STANDARD EQUIPMENT**

**POWERTRAIN**-Diesel engine, CAT C4.4 Twin Turbo-down function-certified to EPA Tier4 Final,-Three stage fuel filtration system with-EU Stage IV, MLIT 2014-water separator and indicator-- Three selectable power modes-3000m (9840ft) altitude capability-capability; HHP, STD and ECO-without de-rate-- After-treatment system: CEM (DOC-52 deg. C (126F) high ambient cooling-- + DPF + SCR) and DEF System-capability with de-rate from-(DEF Tank and DEF Lines)-48 deg. C (118F)-Variable fan speed control with-85 amp. Alternator-viscous clutch-Radial seal air filter with double-One touch low idle with Automatic Engine-filter element-speed Control (AEC)-Electric fuel lifting pump-Automatic (programmable) idling shut-Capability of using Bio-Diesel fuel(B20)

**UNDERCARRIAGE**-HD track rollers-(ISO 15818 compliant)-Grease lubricated track link-Swivel guard-Tie down points on base frame

**HYDRAULICS**-Electric boom regeneration circuit-Reverse swing damping valve-Stick regeneration circuit-High performance hydraulic return filter-One touch lifting mode-(Capsule filter type)-Automatic two speed travel-CRN compliant accumulator-Boom and stick drift reduction valve

**ELECTRICAL**-Maintenance free battery-working lights (halogen); Base machine-Centralized electrical disconnect switch-frame (one), Cab mounted (two),-CAT Product Link-Boom mounted both sides (two)-90 seconds programmable time delay

**OPERATOR ENVIRONMENT-CAB**:-distortion free rear view camera-Sound suppressed ROPS cab (ISO 12117-2-picture-compliant) with viscous mount-Automatic bi-level air conditioner with-Openable skylight as emergency exit-pressurized function-(Dual exit hatch)-24V radio ready (1DIN size, stereo-Openable laminated front upper-speakers, antenna-flexible type)-windshield w/ assist device-12V x 2 power supply with sockets-Removable tempered lower windshield-(Maximum 10 amp.)-with in cab storage bracket-Roll Down Sun Screen, Washable Floormat-High back seat with air suspension, seat-Interior utilities (Interior lighting,-heater and head rest-Coat hook, Beverage holder, Literature-Fully adjustable seat, console and armrest-holder, Document holding space, and-51MM (2") width seat belt-Cab rear storage compartment)-Full graphic 7inch LCD monitor, with

**SAFETY AND SECURITY**-Rearview camera with three mirrors-Anti-skid Plate-(ISO 5006 compliant) and one additional-Neutral lever(lock out)for all controls-hand rail mirror for right rear view-Ground level accessible secondary engine-RH Hand rail and hand hold (ISO 2867-shutoff switch in cab-compliant)-Signaling/ Warning horn, Jump Start Stud-Bolt free service platform with-Safety hammer for cab evacuation

**OTHER STANDARD EQUIPMENT**-Engine oil, Fuel, and Hydraulic oil-located separately)-filters grouped for ease of-Sampling ports for Scheduled Oil-maintenance (Secondary fuel filter is-Sampling (S.O.S)

**MACHINE SPECIFICATIONS**

<b>Description</b>	<b>Reference No</b>
325F L CR HEX AM-N BCF1	541-7386
REACH BOOM HD PKG	483-8070
TRACK, 31" TG HD (GLT) PRESS	357-7481
GUARD, TRACK GUIDE, SEGMENTED	346-7148
CIRCUIT, COMBINED, STP PKG	541-7332
PILOT LINES, BKT CLOSE PGQC	536-9525
LINE, PUMP SUCTION	538-4102
STARTING, COLD WEATHER	452-0154
GUARD, BOTTOM HD	451-9289
DECALS, EXTERIOR ANSI	452-0157
DECALS, CAB ANSI	500-9507
PRODUCT LINK, CELLULAR PL641	460-1148
LINES-HP, REACH BOOM	451-7537
LINES, HP, R9'6" STICK	356-8117
CTRL,CAT PIN GRAB COUPLER ANSI	500-4192
LINES-QC, REACH BOOM	451-7540
LINES, QC, R9'6" STICK	242-6490
CHANGER,HAND CTRL 2-WAY (ANSI)	458-3345
INSTRUCTIONS, ENGLISH	0P-3380
STORAGE PROTECTION (EXPORT)	0G-4126
LANE 3 ORDER	0P-9003
ROLL ON-ROLL OFF W/O BKT QC B1	0G-0481
Cat 48" Bucket	
Cat H-120 HDY Hammer	
Cat HDY Thumb	

---

Sell Price	\$315,944.06
<b>Net Balance Due</b>	<b>\$315,944.06</b>
Ext Warranty	Included
HET: HET POTTER/RANDL TAX (0.153%)	\$483.39
<b>After Tax Balance</b>	<b>\$316,427.45</b>

---

**WARRANTY**

Standard Warranty:        Standard 12 Month Unlimited Hour Full Machine Coverage

Extended Warranty:        325 NONGOVERNMENT 36 / 5000 PREMIER

**F.O.B/TERMS**

Amarillo

Accepted by \_\_\_\_\_ on \_\_\_\_\_

\_\_\_\_\_  
Signature