



Quote 200134-01

August 7, 2018

HBRK Associates

Attention:Richard

Dear Richard, Thank you for this opportunity to quote Caterpillar products for your business needs. We are pleased to quote the following for your purchase consideration.

One (1) New CATERPILLAR Model: 272D2 XHP Skid Steer Loaders | Compact Track Loaders with all standard equipment in addition to the additional specifications listed below:

STOCK NUMBER:C92119

We wish to thank you for the opportunity of quoting on your equipment needs. This quotation is valid for 30 days, after which time we reserve the right to re-quote. If there are any questions, please do not hesitate to contact me.

Sincerely,

Jay West
Machine Sales Representative

One (1) New CATERPILLAR Model: 272D2 XHP Skid Steer Loaders | Compact Track Loaders with all standard equipment in addition to the additional specifications listed below:

STANDARD EQUIPMENT

POWERTRAIN-Cat C3.8 Turbo Aftercooled Diesel Engine-S-O-S Sampling Valve, Hydraulic Oil-- Gross Horsepower per SAE J1349-Filter, Cartridge Type, Hydraulic-110 hp (82 kW) @ 2400 RPM-Filters, Cartridge Type, Fuel-- EPA Tier 4 Final and EU Stage IV-and Water Separator-Certified with Aftertreatment-Radiator/Hydraulic Oil-- Electric Fuel Priming Pump-Cooler (side-by-side)-- Air Inlet Heater Starting Aid-Spring Applied, Hydraulically Released,-- Liquid Cooled, Direct Injection-Parking Brakes-Two Speed Travel with Ride Control-Hydrostatic Transmission-Air Cleaner, Dual Element, Radial Seal-Four Wheel Chain Drive

HYDRAULICS-HYDRAULICS, XHP-- Worktool Harness-- High Flow: 40 gpm (150 lpm) max-CONTROLS:-- High Flow Pressure: 4061 psi-Electro/Hydraulic Implement Control, RH-28000 kPa max-Electro/Hydraulic Hydrostatic-- Continuous Flow-Transmission Control, LH-- Hydraulics, Proportional

STARTERS, BATTERIES, AND ALTERNATORS-1000 CCA Heavy Duty Battery w/Disconnect

ELECTRICAL-12 Volt Electrical System-- Two Rear Halogen Working Lights-100 Ampere Alternator-- Two Adjustable Front Halogen Lights-Ignition Key Start / Stop / Aux Switch-- Dome Light-Lights:-Backup Alarm-- Gauge Backlighting-Electrical Outlet, Beacon-- Two Rear Tail Lights

OPERATOR ENVIRONMENT-Operator Warning System Indicators:-- Hydrostatic Transmission Disables-- Air Filter Restriction-- Parking Brake Engages-- Alternator Output-ROPS Cab, Enclosed (C3), Tilt Up:-- Armrest Raised / Operator Out of Seat-- Air Conditioner incl Heater/Defroster-- Engine Coolant Temperature-- Side Windows-- Engine Oil Pressure-- Cup Holder-- Air Inlet Heater Activation-FOPS, Level I-- Hydraulic Filter Restriction-Top and Rear Windows-- Hydraulic Oil Temperature-Deluxe Headliner-- Park Brake Engages-Floormat-- Engine Emission System-Interior Rear View Mirror-Gauges: DEF Level, Fuel Level,-12V Electric Socket-Hour Meter and Tachometer-Horn-Storage Compartment with netting-Hand (Dial) and Foot Throttle, Electronic-Seat, Comfort, Air Suspension, Cloth,-Dual Direction Electronic Self Level -- Heat-(Raise and lower)-- High Back heated seat with recline-Work Tool Return to Dig-- Lumbar support-Work Tool Positioner-- Fully adjustable Seat Mounted-Electronic Snubbing (Lift)-Controls-Advanced LCD Display-Ergonomic Contoured Armrest-- Full color 5 inch LCD screen-Control Interlock System, when Operator-- Advanced Anti-theft Security System,-Leaves Seat or Armrest Raised:-with 50 user code capability-- Hydraulic System Disables-- Rear View Camera

FRAMES-Lift Linkage, Vertical Path-Support, Lift Arm-Chassis, One Piece Welded-Cast Rear Bumper-Machine Tie Down Points (4)-Ventilated Rear Door with Integrated-Belly Pan Cleanout-Sealing

OTHER STANDARD EQUIPMENT-Engine Enclosure - Lockable-with Integrated Pressure Release-Extended Life Antifreeze (-37C, -34F)-Split D-Ring to Route Work Tool Hoses-Coupler, Mechanical-Along Side of Left Lift Arm-Hydraulic Oil Level Sight Gauge-Variable Speed Hydraulic Cooling Fan-Radiator Coolant Level Sight Gauge-Per SAE J818-2007 and EN 474-3:2006 and-Radiator Expansion Bottle-ISO 14397-1:2007-Cat Tough Guard Hose-At 50% Tipping Load-Heavy Duty Flat Faced Quick Disconnects-- 3650 lb (1656 kg)

MACHINE SPECIFICATIONS

Description	Reference No
272D2 XHP SKID STEER LOADER	435-8973
CONVERSION ARRANGEMENT	421-0340
CERTIFICATION ARR, P65	563-1163
FILM, SELF LEVEL, ANSI	435-9238
FILM, RIDE CONTROL, ANSI	422-3445
DOOR, CAB, POLYCARBONATE	345-6260
RADIO, AM/FM, BLUETOOTH	345-6180
LIGHTS, LED	495-1671
SEAT BELT, 2"	258-4095
PRODUCT LINK, CELLULAR PL240	441-4818
FAN, COOLING, DEMAND, REVERSING	457-2835
TIRES, 14/17.5 CAT 14PR	331-2490
QUICK COUPLER, HYDRAULIC	515-8592
SERIALIZED TECHNICAL MEDIA KIT	421-8926
HEATER, ENGINE COOLANT, 120V	345-3556
INSTRUCTIONS, ANSI, USA	435-8840
LANE 3 ORDER	0P-9003
Cat 84" Bucket	

Sell Price	\$70,274.42
Net Balance Due	\$70,274.42
HET: HET POTTER/RANDL TAX (0.153%)	\$107.52
After Tax Balance	\$70,381.94

WARRANTY

Standard Warranty: Standard 12 Month Unlimited Hour Full Machine Coverage

F.O.B/TERMS

Amarillo

Accepted by _____ on _____

Signature