

./en).

DriveCore Install Analog Series

The new DriveCore™ Install series amplifiers is a complete line of high performance installation amplifiers based on Crown's proprietary DriveCore technology.



([REDACTED])

DCi 2|300 ([REDACTED])

Two-channel, 300W @ 4Ω Analog Power Amplifier, 70V/100V

compare

front left & Right



([http://www.\[REDACTED\]](http://www.[REDACTED]))

DCi 2|600 ([http://\[REDACTED\]](http://[REDACTED]))

Two-channel, 600W @ 4Ω Analog Power Amplifier; 70V/100V



([REDACTED])

DCi 8|600 ([REDACTED])

Eight-channel, 600W @ 4Ω Analog Power Amplifier, 70V/100V

compare

Subs x 2



([http://www.\[REDACTED\]](http://www.[REDACTED]))

DCi 2|1250 ([http://\[REDACTED\]](http://[REDACTED]))

Two-channel, 1250W @ 4Ω Analog Power Amplifier, 70V/100V

compare



([REDACTED])

DCi 4|1250 ([REDACTED])

Four-channel, 1250W @ 4Ω Analog Power Amplifier, 70V/100V

compare

Compare Selected Products


Select 2 to 4 products to compare

[\(/en\)](#)

Product Comparison

Fronts L&R

2 x Subs

	DCi 2 600 (/en/products/dci-2-600)  (/en/products/dci-2-600)	DCi 2 1250 (/en/products/dci-2-1250)  (/en/products/dci-2-1250)
Product type	Two-channel, 600W @ 4Ω Analog Power Amplifier; 70V/100V	Two-channel, 1250W @ 4Ω Analog Power Amplifier, 70V/100V
Frequency Response (8 Ohms, 20 Hz - 20 kHz)	+/- 0.25 dB	+/- 0.25 dB
Signal To Noise Ratio (A-weighted)	> 108 dB	> 108 dB
Total Harmonic Distortion (at full rated power, 20 Hz - 20 kHz)	0.35%	0.35%
Voltage Gain	34 dB	34 dB
Damping Factor (20 Hz to 100 Hz)	>1000	>1500
Input Impedance (nominal balanced, unbalanced)	10 kOhms, 5 kOhms	10 kOhms, 5 kOhms
Maximum Input Level before Compression	+20 dBu	+20 dBu
Maximum Input Level before Clipping	+26 dBu	+26 dBu
Load Impedance		

(Stereo/Dual Mode)	2 - 16 Ohms; 70Vrms and 100Vrms	2 - 16 Ohms; 70Vrms and 100Vrms
Load Impedance Bridge Mono	4 - 16 Ohms; 140Vrms and 200Vrms	4 - 16 Ohms; 140Vrms and 200Vrms
Cooling	Continuously variable speed forced air, front to back airflow	Continuously variable speed forced air, front to back airflow
Maximum Fan Noise (re dBA SPL @ 1M)	45	45
Required AC Mains (+/- 10%)	100V-240V ~ 50/60 Hz	100V-240V ~ 50/60 Hz
Dimensions	19" x 3.5" x 14.25" (48.3cm x 8.9cm x 35.63cm)	19" x 3.5" x 14.25" (48.3cm x 8.9cm x 35.63cm)
Weight	18lbs (8.53kg)	23.5lbs (10.66kg)
IEC Power Connector	15A	15A

<http://www.amx.com>

© 2015 HARMAN International Company. All Rights Reserved.

<http://www.harman.com>

<http://www.bssaudio.com>

<http://www.dbxpro.com>

<http://www.lexicon.com>

<http://www.martin.com>

<http://www.soundcraft.com>

<http://www.studer.ch>

<http://www.hiqnet.com>